



CALYPSO Filter Grade H

For high-performance filtration, particle removal down to 0.01 micron, oil removal down to 0.1 mg/m³ at 20 deg C

Model	m ³ /h	Connection	Weight	Width	Height	Price	Spare-	Price
		R	KG	mm	mm	€	element	€
H 10	39	1/2"	1,4	87	209	95	EH 10	30
H 15	57	1/2"	1,4	87	209	105	EH 15	33
H 20	79	1/2"	1,4	87	209	117	EH 20	37
H 30	118	3/4"	1,7	87	279	133	EH 30	47
H 55	198	1"	4,2	130	315	207	EH 55	63
H 95	342	1 1/2"	4,8	130	415	237	EH 95	77
H 150	540	1 1/2"	5,6	130	515	266	EH 150	99
H 220	799	1 1/2"	8,4	130	715	397	EH 220	125
H 290	1047	2"	11,4	164	823	541	EH 290	163
H 430	1569	2 1/2"	13	164	1073	665	EH 430	209
H 625	2250	3"	20	250	1052	1,378	EH 625	271
H 775	2797	3"	27,5	250	1202	1,477	EH 775	356

CALYPSO Filter Grade S

For high-performance filtration, particle removal down to 0.01 micron, oil removal down to 0.001 mg/m³ at 20 deg in conjunction with filter grade H

Model	m ³ /h	Connection	Weight	Width	Height	Price	Spare-	Price
		R	KG	mm	mm	€	element	€
S 10	39	1/2"	1,4	87	209	95	ES 10	30
S 15	57	1/2"	1,4	87	209	105	ES 15	33
S 20	79	1/2"	1,4	87	209	117	ES 20	37
S 30	118	3/4"	1,7	87	279	133	ES 30	47
S 55	198	1"	4,2	130	315	207	ES 55	63
S 95	342	1 1/2"	4,8	130	415	237	ES 95	77
S 150	540	1 1/2"	5,6	130	515	266	ES 150	99
S 220	799	1 1/2"	8,4	130	715	397	ES 220	125
S 290	1047	2"	11,4	164	823	541	ES 290	163
S 430	1569	2 1/2"	13	164	1073	665	ES 430	209
S 625	2250	3"	20	250	1052	1,378	ES 625	271
S 775	2797	3"	27,5	250	1202	1,477	ES 775	356