



CALYPSO Filter Grade C

For oil vapour and odour removal (activated carbon)
oil removal down to 0.003 mg/m³ at 20 deg C

applicable in oil lubricated compressors in conjunction with filter grade H

Model	m ³ /h	Connection	Weight	Width	Height	Price	Spare-	Price
		R	KG	mm	mm	€	element	€
C 10	39	1/2"	1,4	87	209	95	EC 10	30
C 15	57	1/2"	1,4	87	209	105	EC 15	33
C 20	79	1/2"	1,4	87	209	117	EC 20	37
C 30	118	3/4"	1,7	87	279	133	EC 30	47
C 55	198	1"	4,2	130	315	207	EC 55	63
C 95	342	1 1/2"	4,8	130	415	237	EC 95	77
C 150	540	1 1/2"	5,6	130	515	266	EC 150	99
C 220	799	1 1/2"	8,4	130	715	397	EC 220	125
C 290	1047	2"	11,4	164	823	541	EC 290	163
C 430	1569	2 1/2"	13	164	1073	665	EC 430	209
C 625	2250	3"	20	250	1052	1,378	EC 625	271

Prices for filters include internal automatic drain, stage C without Calypso Filter model 10 to 30 with differential slide indicator Calypso Filter model 55 to 775 with differential pressure gauge

Calypso Filters comply to the European Pressure Equipment Directive, PED 97/23/EC

Max. operating pressure 16 bar g

Max. operating temperature 60° C