



**Refrigeration Dryer Series CAD**

	CAPACITY		CONNECT	POWER	DIAMETERS (mm)			WEIGHT
	M3/min	M3/h	INCH	KW	W	L	H	KG
CAD 8	0.48	3	1/2'	0.22	370	525	520	27
CAD 12	0.73	44	1/2'	0.25	370	525	520	32
CAD 21	1.20	72	3/4'	0.26	350	500	450	25
CAD 30	1.83	110	3/4'	0.28	350	500	450	27
CAD 42	2.50	150	1'	0.6	370	500	764	44
CAD 53	3.10	186	1'	0.67	370	500	764	44
CAD 61	3.60	216	1 1/2'	0.79	460	560	789	53
CAD 70	4.10	246	1 1/2'	0.87	460	560	789	60
CAD 91	5.40	324	1 1/2'	1	460	560	789	65
CAD 110	6.50	390	1 1/2'	1.2	580	590	899	80
CAD 130	7.70	462	1 1/2'	1.44	580	590	899	80
CAD 170	10.00	600	2'	1.8	735	898	962	128
CAD 200	12.00	720	2'	2	735	898	962	146
CAD 250	15.00	900	2'	2.6	735	898	962	158
CAD 301	18.00	1080	2'	3.5	735	898	962	165
CAD 401	24.00	1440	3'	3.9	1020	1082	1535	325
CAD 500	30.00	1800	3'	4.45	1020	1082	1535	335
CAD 585	35.00	2100	3'	5.5	1020	1082	1535	350
CAD 850	50.00	3000	DN 125	6.8	1020	2099	1535	550
CAD 1150	70.00	4200	DN 125	10.2	1020	2099	1535	600

**Reference data according to DIN/ISO 7183**

Air flow m<sup>3</sup>/h in relation to 20° C and 1 bar a

Operating pressure: 7 bar g Inlet temperature: 35° C Ambient temperature: 25° C

Operating conditions:

Max. inlet temperature: 55° C

Min./max. ambient temperature: +3° C / + 45° C

\*Bigger refrigeration dryers on request